„Рафинерија уља Модрича" а.д. Модрича
Војводе Степе Степановића 49
74480 Модрича, РС
Босна и Херцеговина

Тел: +387 53 810 111
Факс: +387 53 812 541
info@modricaoil.com
www.modricaoil.com

Subject: **Technical task for the procurement of raw materials for 2026 – Order 148/26**

Date: 29. 10. 2026.

Product name: **Base Oil – Group II – 6 cSt**

Product name: Viscosity grade:

Product Application: The base oil used in the formulation of motor and industrial lubricants.

Specifications:

The planned amount of base oil (t): **100**
The planned amount of additives (t):
Packaging base oil (delivery): **Autotank**

Delivery: **One-time**
Price:

Characteristics of base oil**:**

Viscosity at 100 ^{O}C (mm^2/s)	**BAS ISO 3104**	**6,0 – 7,5**
Viscosity at 40 ^{O}C (mm^2/s)	**BAS ISO 3104**	**41**
Viscosity Index, min.	**BAS ISO 2909**	**105**
Pour Point, max. (^{O}C)	**BAS ISO 3016**	**-15**
Flash Point, min. (^{O}C)	**ISO 2592**	**230**
Color, max.	**ASTM D 1500**	**L0,5**
Noack test – Volatility, max. (%)	**DIN 51581**	**report**
Appearance	**Visually**	**clear**
Sulphur content, max. (%)	**ASTM D 4294**	**0,001**
Neutralization number, mgKOH/g, max.	**BAS ISO 6618**	**0,02**

Note:

<u>Required technical documentation that must be submitted:</u>

- Technical Data Sheet – TDS,
- Material Safety Data Sheet – MSDS, in accordance with EU Regulative no. 1907/2006
- Technical Report (engine tests and other tests) - Technical report (may be in electronic form as well as other documents at the request of),
- Country of origin – Statement,
- REACH – status,

Tehnical task done: Branko Despotović, MSc
Head of Development, Testing and Quality Signature: