„Рафинерија уља Модрича" а.д. Модрича
Војводе Степе Степановића 49
74480 Модрича, РС
Босна и Херцеговина

Тел: +387 53 810 111
Факс: +387 53 812 541
info@modricaoil.com
www.modricaoil.com

Subject: **Technical task for the purchase of the additives for Hydraulic oils MH for 2026 – Order No. 151/25**

Date: 30. 10. 2026.

Product type: **Hydraulic oils MH**

Product name: **Hidraulično ulje MH**

Viscosity grade: **ISO VG 46**

Product Application: Hidraulično ulje MH 46 is a specially formulated oil for hydraulic systems, with extended drain intervals, up **to 5000 hours**. **Viscosity index > 170**.

Specification: **DENISON HF-0, DIN 51524/2/3, Cincinnati-Machine P-70, Eaton Vickers 35VQ-25, Bosch Rexroth 90220**

Planned amount of final product (t): **92,0**
Planned amount of additives (t):
Adittive packaging (Delivery): **Barrels - Palletized**

Delivery dynamics:
One-time

Required Approval:

Data on the additive that the tenderer must supply:

Name and type of additive:
Recommended dosage (%):
Recommended Base Oils - Group (%)
I II III IV V

Aprovals that can be obtained with the specified additive:
(until Approval is valid)

Note: **Along with additive package there must be an offer for according viscosity improver with recommended dosage. VI > 170.**

<u>Required technical documentation that must be submitted:</u>

- Technical Data Sheet – TDS,
- Material Safety Data Sheet – MSDS, in accordance with EU Regulative no. 1907/2006
- Technical Report (engine tests and other tests) - Technical report (may be in electronic form as well as other documents at the request of),
- Country of origin – Statement,
- REACH – status,

Tehnical task done: Branko Despotović, MSc
Head of Development, Testing and Quality Signature: